

(MARKED UP SPECIFICATION)

Docket # 70177

AXLE SUSPENSION FOR RIGID AXLES OF VEHICLES

Specification: FIELD OF THE INVENTION

The present invention pertains to an axle suspension for rigid axles of vehicles, especially air-suspension, air cushioned or air sprung utility vehicles, in which a twistable, angulatable or torsionable four-point connecting rod, which is connected in an articulated manner to the vehicle axle, on the one hand, and to the vehicle body, on the other hand, and which is connected by two joints located at spaced locations from one another in the transverse direction of the vehicle to the vehicle axle and to the vehicle body, is arranged above the vehicle axle, at least one axle strut, which extends in the longitudinal direction of the vehicle and connects the vehicle axle and the vehicle body in a vertically movable manner, is arranged on each side of the vehicle for axle guidance, and at least one spring assembly unit is arranged between the vehicle axle and the vehicle body for springing or suspension.

BACKGROUND OF THE INVENTION

Such axle suspensions of this type have been known from, e.g., DE 195 21 874.

09890381-032301
5 The design embodiment of such axle suspensions is, in principle, simple, space- and cost-saving, and has consistently proved successful in practice. However, such an axle suspension forming this type as well as other designs known from the prior art have the drawback that the axle is rigidly connected to the axle struts arranged adjacent to same. In conjunction with the entire axle construction, such a fastening leads to a kinematic overdetermination or redundancy, of the degrees of freedom of the vehicle chassis. This in turn leads to the course of the kinetic processes within the axle construction being undefined in certain situations, which may have an adverse effect on the coordination of the chassis and the chassis dynamics in the vertical and lateral directions.

10 Moreover, the kinematic overdetermination may lead to vibrations of the drive shaft with a resulting increase in the wear of the drive shaft and high load of the axle housing used in the case of driven axles.

SUMMARY AND OBJECTS OF THE INVENTION

15 The technical object of the present invention is to improve an axle suspension of this type such that the kinematic conditions are improved in order to optimize the dynamics of the vehicle movement and to achieve reduced vibrations and reduced wear as well as increased lateral rigidity of the axle construction. In addition, the number of the individual parts shall be further reduced, the ease of repair shall be increased and the unsprung or unsuspended weights shall be further reduced.

5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

~~This object is accomplished according to the present invention by the technical teaching of claim 1, in conjunction with the type-forming features.~~ According to the present invention, the axle strut shall be connected to the vehicle axle by a molecular joint. Contrary to the axle constructions known from the prior art, the articulated mounting of the vehicle axle leads to a markedly more favorable elasticity for the entire system of the axle suspension and an unambiguous assignment or association of the kinematic conditions under all driving conditions, so that the inward and outward deflections of the axle as well as the pendular behavior are not adversely affected by squeezing, or jamming, or twisting of the vehicle axle.

~~Special embodiments of the subject of the present invention will also appear from the features of the subclaims.~~

It proved to be especially advantageous, in particular, that the axle struts have a mount or support for the spring assembly unit used and/or a shock absorber. The axle struts are extended for this purpose beyond the articulation point for the end connecting the axle strut to the vehicle axle at their free end not articulated to the vehicle body, and the spring assembly unit usually arranged separately between the vehicle axle and the vehicle body in prior-art constructions is accommodated at this end. The mount or support of the spring assembly unit may have a rigid or articulated design according to the present invention, and

an articulated connection additionally reduces the wear of the spring assembly unit. This functional integration leads, furthermore, to a reduction in the number of components and thus to a reduction of the costs of the entire construction of the axle suspension even as a consequence of reduced assembly time and the stocking of a reduced number of parts. The spring assembly units can be optimally connected to the axle used due to the very simple axle design according to the present invention, and it is conceivable to arrange the axle struts in a V-shaped when viewed in three-dimensional space, which leads to an additional lateral stabilization. It is, of course, conceivable in this connection to provide the axle strut not only with a mount or support for one spring assembly unit, but, e.g., four or more spring assembly units, preferably air spring cushion elements in order to spring or cushion the vehicle axle.

To make it possible to adapt the kinematic conditions of the axle suspension to the design embodiment according to the present invention even better, it is, moreover, advantageous for the axle strut to be also fixed on the vehicle body by a molecular joint. This additional molecular joint should preferably have a stiffer joint characteristic than the vehicle axle-side molecular joint of the axle strut, because a cardanic angulation especially of air bellows used as spring elements is reduced hereby.

In addition, a clean design guiding of the parallelogram of both components is possible due to the spatial kinematics of the upper four-point connecting rod and of the lower

axle strut with two joints, which in turn has a favorable effect on the overall kinematics of the axle and also offers the vehicle manufacturer ideal conditions for installation. In particular, the ideal trapezoid shape guiding guarantees that the wear of the cardan universal-joint shaft is kept as low as possible.

5 Exemplary The various features of novelty which characterize the invention are pointed
out with particularity in the claims annexed to and forming a part of this disclosure. For a
better understanding of the invention, its operating advantages and specific objects attained
by its uses, reference is made to the accompanying drawings and descriptive matter in which
preferred embodiments of the subject of the present invention will be explained in greater
detail below on the basis of the drawings attached. In the drawings,

Figure 1 — shows invention are illustrated.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

15 Figure 1 is a perspective view of a first exemplary embodiment of the axle suspension according to the present invention when viewed obliquely in the front in the direction of the vehicle;

Figure 2 shows is a perspective view of the axle suspension according to Figure 1 when viewed obliquely at the rear;

Figure 3 shows is a top view of another exemplary embodiment of the axle suspension according to the present invention;

Figure 4 shows is a sectional view of a molecular joint used for the axle suspension according to the present invention;

Figure 5 shows is a perspective view of another exemplary embodiment of the axle suspension according to the present invention when viewed obliquely in the front in the direction of the vehicle; and

Figure 6 shows is a view corresponding to the direction of arrow VI in Figure 5, but without the wheel of the vehicle.

Figure 7 is a view similar to that of Figure 6, but with spring assemblies both in front of and behind the vehicle axle.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to the drawings in particular, Figure 1 shows the axle suspension according to the present invention on a utility vehicle chassis, not shown specifically here, which is provided with longitudinal beams 1a, 1b. The longitudinal beams 1a and 1b are arranged at laterally spaced locations from one another and are rigidly connected to one another by the crossbeams 2a, 2b. The vehicle axle 3, which is connected to the longitudinal beams 1a, 1b via a four-point connecting rod 4, is arranged under the longitudinal beams 1a and 1b. The four-point connecting rod 4 has, on the whole, four joints 5, 6, 7 and 8, and two joints 5, 6 each are fastened to the vehicle body and two joints 7, 8 to the vehicle axle. The joints fastened to the vehicle axle and to the body are arranged at spaced locations from one another in the transverse direction of the vehicle.

Figure 1 also shows that a respective side brackets 9 and 10, at the lower, free end of which a respective axle strut 11 and 12 is articulated by means of a molecular joint 13; and 14 each, is fastened to each of the two longitudinal beams 1a and 1b.

A molecular joint is, in principle, a joint as is shown as an example as a ball-and-socket joint in Figure 4. The molecular joint comprises a joint ball 30 located on the inside, a housing 32 surrounding the joint ball, as well as an elastomer 31 arranged between the joint ball 30 and the housing 32. In the exemplary embodiment according to Figure 4, the joint ball 30 has a two-part design, comprising an inner, metallic joint axle 33 and an outer ball 34 consisting of elastomer, which is made in one piece therewith. In another

embodiment of the molecular joint, the joint ball 30 may be made of metal as a whole or it may have a cylindrical inner part instead of a ball. Such molecular joints can be correspondingly adapted to the loads acting on the joint by selecting the elastomer arranged between the joint ball 30 and the housing 32. Moreover, recesses, which bring about a specific effect on the joint characteristics, may be provided within the elastomer and/or the housing or on the inner part of the joint at least in some areas. Thus, molecular joints may have, e.g., a reduced damping in one direction and a correspondingly greater damping in at least one direction located offset in relation thereto.

The axle struts 11, 12 articulated to the side brackets 9, 10 by means of the molecular joints 13, 14 are arranged essentially in the horizontal direction and are connected to the axle 3 according to the present invention at their ends facing away from the molecular joints 13, 14 by means of another molecular joint 15, 16 each. The molecular joints 15, 16 have, in principle, the above-described design and make it possible both to absorb longitudinal and vertical forces and angulations, force acting at an angle or cardanics, which are introduced into the chassis by the movements of the axle. Overdetermination or redundancy of the kinematic degrees of freedom is prevented by the movements of the axle, so that a more optimal forward coordination can be brought about with respect to the chassis dynamics in the vertical and lateral directions.

The view in Figure 2 shows that the axle struts 11, 12 are extended beyond the

art articulation point for the molecular joints 15 and 16 and have a mount 17 and 18 each for a respective spring assembly unit 19, 20 at their free ends. Furthermore, there is a connection between the axle struts 11, 12 and the vehicle body 1a, 1b via a shock absorber 35, 36 each. The extension of the axle struts 11 and 12 with the integration of the mounts 17 and 18 leads to a reduction in the number of components usually used in prior-art axle constructions and thus reduces the amount of parts to be stocked and the assembly times for the axle construction according to the present invention. The mounts 17 and 18 may be rigid, or formed by a ball-and-socket or other type of joint.

The top view of another exemplary embodiment of the axle construction according to the present invention in Figure 3 shows that the axle struts 11 and 12 may have a direction extending toward the middle of the vehicle from their front articulation by means of the molecular joints 13 and 14 to the end of the vehicle when viewed in a top view. Moreover, the position of the four-point connecting rod 4 as well as of its articulation points on the body and the axle can be seen in the top view.

It is, of course, possible to also use the articulation according to the present invention of the axle to the axle struts for constructions in which three, four or more such spring elements are used instead of the two spring assembly units shown and in which the spring assembly units 19, 20 are arranged in front of or behind the vehicle axle 3 when viewed in the direction of the vehicle.

An embodiment with spring assembly units 19, (20) arranged in front of the vehicle axle 3 is shown in Figure 5. The shock absorber 35 (36) is fastened to the mount 18 (17) in this embodiment and the spring assembly unit 19 (20) with an air bellows (air-suspension or air spring) is mounted on the axle strut 12 (11).

List of Reference Numbers:

- 1a—Longitudinal beam
- 1b—Longitudinal beam
- 2a—Crossbeam
- 2b—Crossbeam
- 3—Vehicle axle
- 4—Four-point connecting rod
- 5—Joint
- 6—Joint
- 7—Joint
- 8—Joint
- 9—Side bracket
- 10—Side bracket
- 11—Axle strut

- 12 — Axle strut
- 13 — Molecular joint
- 14 — Molecular joint
- 15 — Molecular joint
- 5 16 — Molecular joint
- 17 — Mount
- 18 — Mount
- 19 — Spring assembly unit
- 20 — Spring assembly unit
- 10 30 — Joint ball
- 31 — Elastomer
- 32 — Housing
- 33 — Joint axis
- 34 — Outer ball
- 15 35 — Shock absorber
- 36 — Shock absorber

~~Axle Suspension for Rigid Axles of Vehicles~~

~~Abstract:~~

While specific embodiments of the invention have been shown and described in detail to illustrate the application of the principles of the invention, it will be understood that the invention may be embodied otherwise without departing from such principles.

ABSTRACT OF THE DISCLOSURE

An axle suspension for rigid axles of vehicles, especially air-suspension (e.g., with air shock absorbers/ air springs) utility vehicles, is presented, in which a ~~said~~ twistable four-point connecting rod (4), which is connected in an articulated manner to the ~~said~~ vehicle axle (3), on the one hand, and to the ~~said~~ vehicle body (1a, 1b), on the other hand, and which is connected to the ~~said~~ vehicle axle (3) and to the ~~said~~ vehicle body (1a, 1b) by ~~two~~ four said joints (5, 6, 7, 8) each located at spaced locations from one another in the transverse direction of the vehicle; The four-point connecting rod is arranged above the ~~said~~ vehicle axle (3); a ~~At least one~~ ~~said~~ axle strut (11, 12), which extends in the longitudinal direction of the vehicle and connects the ~~said~~ vehicle axle (3) to the ~~said~~ vehicle body (1a, 1b) in a vertically movable manner, is arranged on each side of the vehicle for guiding the axle ~~and~~ a ~~At least one~~ ~~said~~ air spring assembly unit (19, 20) is arranged between the ~~said~~ vehicle

09/890381-082301

axle (3) and the said vehicle body (1a, 1b) for spring suspension, ~~wherein~~ wherein The axle struts 11, 12 are each connected to the vehicle axle (3) by a molecular joint (15, 16 ~~each~~.

) The articulated mounting of the vehicle axle leads to a markedly more favorable elasticity for the entire system of the axle suspension and to an unambiguous assignment of the kinematic conditions under all driving conditions, so that an inward and outward deflection of the axle as well as the pendular behavior are not adversely affected by squeezing or jamming of the vehicle axle.

70177.2

(MARKED UP CLAIMS)

1. ~~A~~ An axle suspension for a rigid ~~axles of vehicles~~ vehicle axle, especially of air-
suspension utility vehicles, in which the axle suspension comprising:

a said twistable four-point connecting rod (4), which is connected arranged above the
vehicle axle;

two vehicle axle joints connecting two points of said four-point connecting rod to said
vehicle axle in an articulated manner to the said vehicle axle (3), on the one hand, and to the said
vehicle body (1a, 1b), on the other hand, and which is connected to the said vehicle axle (3) and
to the said vehicle body (1a, 1b) by two said joints (5, 6, 7, 8) each;

two vehicle body joints connecting two points of said four-point connecting rod to a
vehicle body in an articulated manner, said two vehicle axle joints being located at spaced
locations from one another in the a transverse direction of the vehicle, is arranged above the said
vehicle axle (3), at least one said axle strut (11, 12), which extends in the and said two vehicle
body joints being located at spaced locations from one another in a transverse direction of the
vehicle;

an first axle strut extending in a longitudinal direction of the vehicle and connects the said
vehicle axle (3) to the said vehicle body (1a, 1b) in a vertically movable manner, is arranged on
each a first side of the vehicle for guiding the axle and at least one said, said first axle strut
connecting said vehicle axle to said vehicle body in a vertically movable manner;

an second axle strut extending in a longitudinal direction of the vehicle arranged on a
second side of the vehicle for guiding the axle, said second axle strut connecting said vehicle axle
to said vehicle body in a vertically movable manner;

a spring assembly unit (19, 20) is arranged between the said vehicle axle (3) and the said
vehicle body (1a, 1b) for spring suspension;

characterized in that

the said axle struts (11, 12) are connected to the;

a first molecular joint connecting said first axle strut to said vehicle axle (3) by;

a said second molecular joint (15, 16) each.

2. Axle connecting said second axle strut to said vehicle axle.

2. An axle suspension in accordance with claim 1,
characterized in that

the said axle struts (11, 12) have a said mount ?? (17, 18) for the further comprising another
spring assembly unit arranged between the vehicle axle and the vehicle body for spring
suspension, said first axle strut having a first mount for said spring assembly units (19, 20) or said
shock absorbers (35, 36).

3. Axle unit and said second axle strut having a second mount for said another spring assembly
unit.

3. An axle suspension in accordance with claim 2,

09890381.032301

characterized in that

~~the said mounts (17, 18) for the said spring assembly units (19, 20) or the said shock absorbers (35, 36) are designed as joints.~~

4. Axle wherein said first mount includes a joint and said second mount includes a joint.

4. An axle suspension in accordance with claim 3,

characterized in that

wherein the joints are ball-and-socket joints.

5. A An axle suspension in accordance with one of the above claims, characterized in that

~~the said axle struts (11, 12) are additionally connected to the said vehicle body (1a, 1b) via at least one claim 1, further comprising a first shock absorber (35, 36) each.~~

6. Axle connected between said first axle strut and the vehicle body and a second shock absorber connected between said second axle strut and the vehicle body, said first axle strut having a first mount for said first shock absorber and said second axle strut having a second mount for said second shock absorber.

6. An axle suspension in accordance with one of the above claims,

characterized in that

~~the said axle struts (11, 12) is connected to the claim 1, further comprising:~~

a third molecular joint connecting said first axle strut to said vehicle body (1a, 1b) by; and a said forth molecular joint (13, 14) each.

7. Axle connecting said second axle strut to said vehicle body.

7. An axle suspension in accordance with claim 6, characterized in that the wherein said third molecular joint connecting said first axle strut to said vehicle body-side molecular joint (13, 4) of the said axle strut (11, 12) body has a stiffer joint characteristic than the said first molecular joint connecting said first axle strut to said vehicle axle-side axle and said forth molecular joints (15, 16) of the said axle strut (11, 12).

8. Axle joint connecting said second axle strut to said vehicle body has a stiffer joint characteristic than said second molecular joint connecting said second axle strut to said vehicle axle.

8. An axle suspension in accordance with one of the above claims 1,

characterized in that

~~the wherein said spring assembly unit (19, 20) is arranged in front of or behind the said vehicle axle (3).~~

9. A An axle suspension in accordance with one of the claims 1 through 7, characterized in that

a, wherein said spring assembly unit (19, 20) each is arranged in front of and behind the said

vehicle axle (3).

09890391 082801